

# AUTOFLEX 1.9 POWERED FLEXIBLE CONVEYOR TRANSPORTATION

v1.1

**A convenient and safe powered conveyor solution designed for flexible loading, unloading, transport, and assembly.**

The Milwaukee Conveyor 1.9 Powered Autoflex offers customers unmatched flexibility in conveyance.

Designed primarily for the fast and safe loading and unloading of packages in and out of dock trailers, Autoflex is also ideal for both temporary and permanent assembly lines, peak or seasonal workflows, and for creating efficient, spaced-out work areas.

With its simple mobility and flexibility, Autoflex adapts easily to a variety of applications; it's easy to expand, curve, contract, and relocate quickly to other areas or store as needed.



## STANDARD FEATURES

- **Widths:** 30" (optional 24" available)
- **Configurable Units:** Each unit can be set up as either a parent or child configuration.
- **Interlock Sockets:** Input and output interlock sockets included for seamless operation.
- **Push-Button Controls:** Convenient push-button control located at both the infeed and discharge ends.
- **End-of-Line Sensing:** Integrated end-of-line sensing for enhanced efficiency and safety.
- **Ergonomic Design:** Handles on every leg support for easy maneuverability.
- **Advanced Motor Technology:** Powered by 24V DC brushless motor technology.
- **Load/Unload Convenience:** Equipped with a pull bar at the load/unload end for easy handling.
- **Mechanical Connections:** Hook and rod couplers included for secure mechanical connections.
- **Electrical Connections:** 7/8" male and female plugs for connecting multiple systems.

24" Roller Width	30" Roller Width	Leg QTY	Conv Length Expanded	Conv Length Collapsed
MCAFI.92422PT	MCAFI.93022PT	8	22'	10'
MCAFI.92440PT	MCAFI.93040PT*	13	40'	17'
MCAFI.92460PCT	MCAFI.93060PCT	21	60'	27'
MCAFI.92480PCT	MCAFI.93080PCT*	26	80'	34'
MCAFI.924100PCCT	MCAFI.930100PCCT	34	100'	44'
MCAFI.924120PCCT	MCAFI.930120PCCT*	39	120'	52'

## STANDARD SPECIFICATIONS

**Capacity:** 50 lbs. per foot / 100 lbs. per package.

**Speed Options:** Seven operator-controlled speeds, up to 115 feet per minute (FPM)

**Height:** Adjustable from 28.5" to 38.5".

**Locking Casters:** 6" locking casters on every wheel for stability and mobility.

**Operator Controls:** Start, stop, and speed adjustment for precise operation.

**Mode Selector:** Parent/Child mode selector switch for versatile configurations.

**Roller Centers:** 5" centers standard, with optional 4"

## STANDARD LENGTHS:

Standard Systems expanded

- Parent 22'L
- Parent 40'L
- Parent + Child-1 60'L
- Parent + Child-1 80'L
- Parent + Child-1 + Child-2 100'L
- Parent + Child-1 + Child-2 120'L

### MILWAUKEE CONVEYOR

N8069 County Road F #109

Ixonia, WI 53036

**Email:** [jocain@milwaukeeconveyor.com](mailto:jocain@milwaukeeconveyor.com)

**Phone:** 262-527-3029

**Website:** [milwaukeeconveyor.com](http://milwaukeeconveyor.com)

